

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED
= ISO 9001 =

Name: MC5637H5 Carboflame Coverall	Code: 35283	MC56 CARBOFLAME CLOTHING
---	--------------------	---------------------------------

Description




Coverall with shirt collar, outer fabric in 87% cotton, 12% nylon and 1% carbon fibre, 255 g/m², with concealed two-way central zipper closure with flap and Velcro, chest pockets with zip and flaps with Velcro, loop for gas detector; pocket on left sleeve with flap and Velcro, frontal slanted pockets with flaps and Velcro, hidden exterior-to-interior access. Two back pockets with flaps and Velcro, elastic waistband. Knee pad pockets with Velcro closure, ruler pocket with flap and Velcro, reflective band on the shoulders, legs and arms, triple stitching.

- The entire Carboflame series is Flame Retardant and antistatic, suitable for protecting the operator from accidental contact with minor flames, molten metal splashes and accidental electric contact of short duration.
- Night safety thanks to the reflective bands.

In combination with the coverall, is it possible to wear our under garments: Carboflame undershirt art. MC5610 and Carboflame underpants art. MC5620, meeting the point A.2 of IEC 61482-2 which is stating that the electric arc protective clothing shall be used with under garments made of materials that would not melt with the arc.

The product is designed and manufactured according to the Regulation (EU) 2016/425 and subsequent amendments.
It is classified as PPE Cat.III.



Category III	Colours Orange	Available Sizes XS-3XL
Quantity/Carton 15	Important Information Keep in a cool dry place, far from heat sources and direct light. Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Petrochemical Industry, Oil & Gas Industries, Mining Industry.
Dexterity	EC Standards EN 1149-5  EN ISO 11612  Limited Flame Spread:A1 Convective Heat:B1 Radiant Heat:C1 Contact Heat:F1 CEI EN 61482-1-2  Class:1	Storage and cleaning We recommend to follow the washing instructions. 