



Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441 export@sirsafety.com www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED
= ISO 9001 =

Name: MC5627H5 Light Carboflame Coverall

Code: 35282

MC56 CARBOFLAME CLOTHING

Description

Coverall with shirt collar in 99% cotton, 1% carbon fibre, 230 g/m². two-way central zipper closure with flap and Velcro, chest pockets with zipper and flaps with Velcro, loop for gas detector above right pocket; pocket on left sleeve with flap and Velcro, frontal slanted pockets with flaps and Velcro, hidden exterior-to-interior access, elastic waistband. Two back pockets with flaps and Velcro, knee pad pockets with Velcro closure; ruler pocket with flap and Velcro, reflective band on the shoulders, legs and arms, triple stitching.

- The Light Carboflame Coverall guarantees a high level of protection while maintaining lightness and breathability of the fabric.
- It is suitable for welding processes.
- Ensures great comfort, thanks to the percentage of cotton used.
- Night safety thanks to the reflective bands.

The product is designed and manufactured according to the Regulation (EU) 2016/425 and subsequent amendments.

Class:1 Values:A1

Limited Flame Spread:A1 Convective Heat:B1 Radiant Heat:C1

EN ISO 11612



It is classified as PPE Cat.II.		
Category	Colours	Available Sizes
II	Orange	XS-3XL
Quantity/Carton	Important Information	Recommended for
15	Keep in a cool dry place, far from heat sources and direct light. Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it.	Petrochemical Industry, Oil & Gas Industries, Mining Industry.
Dexterity	EC Standards EN 1149-5	Storage and cleaning We recommend to follow the washing instructions.
	EN ISO 11611	