

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciaci, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED
= ISO 9001 =

Name: MB1823 Zenit Low Shoe	Code: 22032	MB18 FOOTWEAR TOTAL PLANE SERIES
------------------------------------	--------------------	---

Description

Dissipative footwear in class 2, low model with 200 joule composite toecap and Zero Penetration composite midsole. Extra strong nubuck leather upper.

REACTOR sole: Polyurethane/TPU sole. The open-cell polyurethane (PU) insole allows for a high shape memory effect and provides a cushioning effect. The TPU outsole provides flexibility, softness, as well as mechanical and chemical resistance. Especially after prolonged use, it enhances forefoot flexibility for a more natural motion, reducing fatigue.

Anti-slip SRC standard.

EVA SOFT 3 MM INSOLES, with anti-weariness properties; interchangeable, ensuring continued hygiene and cleanliness.

AIRMIX Insoles: anatomic insoles, made of three materials with variable thickness, allow for excellent air circulation, even after prolonged use.

3D-TEX LINING for foot ventilation, reducing perspiration.

Main features:



- ESD
-
- Curved sole to facilitate grip and walking
- Innovative design
- Total support of the outsole on the ground
- Open angles to help releasing the impurities
- Outsole with high memory performance
- Outsole in TPU, resistant to oils and hydrocarbons
- Grooves with open angles to discharge any accumulation
- Horizontal grooves to improve flexibility and movements
- Outsole in igh mechanical resistance and long-lasting TPU
- Grooves pattern for better draining of liquids
- Anti-slip SRC standard

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments, and to conform to the requirements of European standards EN ISO 20345 and CEI EN 61340 - Dissipative Footwear Class 2. It is classified as PPE Cat. II.



Category II	Colours Black	Available Sizes 39-47
-----------------------	------------------	--------------------------

Quantity/Carton 10	Important Information Keep the footwear dry and clean in an appropriate environment at ambient temperature. The wet footwear should never be placed in direct contact with a heat source after use, but shall be air-dried in a ventilated environment at ambient temperature. Make sure footwear is in good condition, before use. If the shoes are damaged, replace them.	Recommended for Industrial plants, Construction and Road Work Sites, Logistics and Handling.
------------------------------	---	---

Dexterity	EC Standards EN ISO 20345  Safety Class:S3 SRC CEI EN 61340 	Storage and cleaning Clean the footwear with a soft brush and water. Do not use any substance such as alcohol, methyl ethyl ketone, thinners, gasoline, petrol or any other type of chemicals that could damage the materials, causing non-visible weakenings and compromise the original protective features.
-----------	--	---