

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciaci, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

[export@sirsafety.com](mailto:export@sirsafety.com)  
[www.sirsafety.com](http://www.sirsafety.com)

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED  
= ISO 9001 =

<b>Name: FC1312 Stark 1 Earmuffs</b>	<b>Code: 51191</b>	<b>FC13 EAR PROTECTION EAR MUFFS</b>
--------------------------------------	--------------------	--------------------------------------

### Description

The earmuffs feature hypoallergenic polyurethane cushions with a large contact surface. It is height adjustable, the smallest of the Stark range, suitable for low noise level environments. Weight: 215 g.

SNR 28 dB

Hertz frequency: H Attenuation = 34

Hertz frequency: M Attenuation = 30

Hertz frequency: L Attenuation = 23

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:125/19.1/2.2/16.9;

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:250/22.4/2.5/19.9;

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:500/30.1/2.0/28.1;

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:1000/38.9/2.3/36.6;

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:2000/33.4/2.2/31.2;

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:4000/39.6/2.1/37.5;

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:8000/37.6/2.6/35.0;

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments and in such a way as to comply with the requirements prescribed by the standard EN 352.

It is classified as PPE Cat. II.



Category <b>II</b>	Colours Black - Yellow	Available Sizes unica
Quantity/Carton <b>24</b>	Important Information Make sure the device is in good condition before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Suitable for low noise level environments.
Dexterity	EC Standards EN 352-1 CE	Storage and cleaning Keep in a cool dry place, far from heat sources. Clean with a damp cloth and soapy water. Do not use any solvents.