

SOLDADOR S3 FO SR

AC880BSP

CE EN ISO 20345:2022 S3 FO SR

High safety shoe, water-resistant WPA leather thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining.

High visibility fabric insert. Lined and padded tongue.

Shoe with cross protective leather cover tongue and side closing by click buckle.

TOECAP 200J polymeric composite non-thermic according to EN 22568

MIDSOLE flexible antiperforation composite fabric according to EN 22568

SOLE ACTION bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping SRC

INSOLE 4001, Comfort insole, perspiring, removable, anatomic, absorbing, antistatic ed antibacterial. Electrical resistance: the values found prove that this insole is ESD


FO sole resistance to hydrocarbons

SR sole resistance against slipping

Size 39-47 **Shoe weight** Sz 42 **gr. 635**



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS

 WOOD METAL CARPENTRY  BUILDING AND HEAVY INDUSTRY  WELDER

SOLE



Action is a shoe studied for external jobs, with soft lines making it very light and comfortable.

ANTISLIPPING TEST RESULTS



SRC

ANTI-SLIPPING SOLE

SRA ceramic + NaLS	HEEL >= 0,28	0,39
	FLAT >= 0,32	0,36
SRB steel + glycerol	HEEL >= 0,13	0,26
	FLAT >= 0,18	0,22